



- NOTES: 1. WHERE NO WALL OR BUILDING EXISTS, A 6" HIGH CURB OR BUMPER GUARD IS REQUIRED SO THAT NO PART OF THE VEHICLE EXTENDS OVER OR BEYOND THE PROPERTY LINE. A 6" X 18" CONCRETE CURB IS REQUIRED BETWEEN AREAS OF VEHICULAR ACTIVITY AND PUBLIC RIGHT-OF-WAY, I.E., STREETS AND ALLEYS.
2. WHERE PARKING ABUTS A PERIMETER WALL/FENCE OR BUILDING, A 6" BUMPER GUARD IS RECOMMENDED TO PREVENT VEHICLE OR STRUCTURE DAMAGE.

A	B	C	C'	D	E*	E'
PARKING ANGLE	STALL WIDTH	STALL	DEPTH	CURB LENGTH	DRIVEWAY WIDTH	
					ONE-WAY	TWO-WAY
30°	10'	19.25'	15'	20'	11'	23'
45°	10'	21.5'	18'	14.2'	13'	23'
60°	10'	22.5'	20'	11.5'	18'	23'

*20' (MIN.) WIDTH WHERE FIRE DEPT. ACCESS IS REQUIRED.

DETAIL NO.
G-3150

CITY OF GOODYEAR
STANDARD DETAIL

APPROVED BY:
Goodyear Standards and
Policies Committee 7/97

PARKING LOT DIMENSIONS

DETAIL NO.
G-3150